

CLAIMS

1. A polarizer containing a dichroic material in a matrix, wherein an in-plane retardation at a measurement wavelength providing no absorption is in a range of 950 to 1350 nm.
5
2. The polarizer according to claim 1, wherein a differential retardation fluctuation (σ) at the measurement wavelength providing no absorption is in a range of -5 nm/mm to 5 nm/mm.
10
3. The polarizer according to claim 1, wherein at the measurement wavelength providing no absorption, a distance between a measurement position providing a maximum value of the in-plane retardation and a measurement position providing a minimum value of the in-plane retardation is in a range not more than 10 mm or not less than 100 mm, and a difference between the maximum value and the minimum value (in-plane retardation variation) is less than 60 nm.
15
4. The polarizer according to claim 1, wherein the measurement wavelength is in a range of 800 to 1500 nm.
20
5. The polarizer according to claim 4, wherein the measurement wavelength is 1000 nm.
6. The polarizer according to claim 1, wherein the matrix is a polymer film.
25
7. The polarizer according to claim 6, wherein the polymer film is a polyvinyl alcohol film.
8. The polarizer according to claim 1, which is chip-cut.
30
9. An optical film comprising the polarizer according to claim 1.
10. The optical film according to claim 9, which further comprises a transparent protective layer, and the transparent protective layer is arranged on at least one surface of the polarizer.
35

11. The polarizing plate according to claim 9, wherein a pressure-sensitive adhesive layer is arranged on at least one outermost surface layer.
12. The optical film according to claim 9, which further comprises at least either
5 a polarization converter or a retardation film.
13. The optical film according to claim 12, wherein the polarization converter is either an anisotropic reflective polarizer or an anisotropic light-scattering polarizer.
- 10 14. A liquid crystal panel comprising at least either the polarizer according to claim 1 or the optical film according to claim 9, wherein the polarizer or the optical film is arranged on at least one surface of a liquid crystal cell.
- 15 15. A liquid crystal display comprising the liquid crystal panel according to claim 14.
16. The liquid crystal display according to claim 15, which has a flat light source for emitting polarized light.
- 20 17. An image display device comprising at least either the polarizer according to claim 1 or the optical film according to claim 9.
18. The image display device according to claim 17, which is an electroluminescent display.
- 25 19. An in-house production method for producing the image display device according to claim 17, which comprises a process of chip-cutting at least either the polarizer according to claim 1 or the optical film according to claim 9 and immediately bonding to the display device.
- 30